Amendment of the Claims

Please cancel claims 3, 8, 13 and 18, and amend the remaining claims as follows.

1 (Currently amended). A sheet feeding apparatus comprising:

a sheet container for containing a plurality of stacked sheets;

an elevation/lowering driving unit for elevating and lowering the sheet container;

a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;

a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;

a position detector for detecting a position of the regulating unit; and

a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit:

and further comprising:

a receiving unit for receiving information according to a lowered amount of the sheet container; and

a storage for storing the received information,

wherein the elevation/lowering driving unit lowers the sheet container by the lowered amount stored in the storage when the position detector detects a change in the position of the regulating unit.

2 (Original). The sheet feeding apparatus according to Claim 1, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

3. Cancelled.

4 (Original). The sheet feeding apparatus according to Claim 1, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

5 (Original). The sheet feeding apparatus according to Claim 1, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.

6 (Currently amended). A sheet feeding apparatus comprising:

sheet containing means for containing a plurality of stacked sheets;

elevation/lowering driving means for elevating and lowering the sheet containing means;

sheet conveying means for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying means by elevating the sheet containing means by the elevation/lowering driving means and conveying the sheets to a predetermined conveyance path;

regulating means provided so as to be slidable on the sheet containing means for

regulating a set position of a sheet;

position detecting means for detecting a position of the regulating means; and contact detecting means for detecting a contact state between the uppermost layer of the sheets contained in the sheet containing means and the sheet conveying means,

wherein the elevation/lowering driving means lowers the sheet containing means when a change in the position of the regulating means is detected by the position detecting means in a state in which the uppermost layer of the sheets contacts the sheet conveying means;

	1.1	•			, ,	4
and	further compr	rising:				
a re	ceiving unit fo	or receiving in	formation accor	ding to a lowere	d amoun	it of the sheet
container; a	<u>ınd</u>					
a st	orage for stori	ng the receive	d information.			

wherein the elevation/lowering driving unit lowers the sheet container by the lowered amount stored in the storage when the position detector detects a change in the position of the regulating unit.

7 (Original). The sheet feeding apparatus according to Claim 6, wherein the elevation/lowering driving means lowers the sheet containing means until the uppermost layer of the sheets and the sheet conveying means are separated when the position detecting means detects a change in the position of the regulating means.

8. Cancelled.

9 (Original). The sheet feeding apparatus according to Claim 6, further comprising measuring means for measuring a dimension of a sheet contained in the sheet containing means based on a detection result of the position detecting means.

10 (Original). The sheet f eeding apparatus according to Claim 6, further comprising clocking means, wherein the elevation/lowering driving means elevates the sheet containing means when a change in the position of the regulating means is not detected for a predetermined time.

11 (Currently amended). An image reading apparatus comprising:

a sheet container for containing a plurality of stacked sheets;

an elevation/lowering driving unit for elevating and lowering the sheet container;

a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;

an image reading unit for reading an image on a sheet conveyed by the sheet conveying unit;

a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;

Nagao et al. USSN 10/772,771 Page 5 of 11

a position detector for detecting a position of the regulating unit; and

a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit:

and further comprising:
a receiving unit for receiving information according to a lowered amount of the sheet
container; and
a storage for storing the received information,
wherein the elevation/lowering driving unit lowers the sheet container by the lowered
amount stored in the storage when the position detector detects a change in the position of the
regulating unit.

12 (Original). The imag e reading apparatus according to Claim 11, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

13. Cancelled.

14 (Original). The imag e reading apparatus according to Claim 11, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

15 (Original). The imag e reading apparatus according to Claim 11, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.

Nagao et al. USSN 10/772,771 Page 6 of 11

16 (Currently amended). An image forming apparatus comprising:

a sheet container for containing a plurality of stacked sheets;

an elevation/lowering driving unit for elevating and lowering the sheet container;

a sheet conveying unit for sequentially taking out the sheets from an uppermost layer put in contact with the sheet conveying unit by elevating the sheet container by the elevation/lowering driving unit and conveying the sheets to a predetermined conveyance path;

an image forming unit for forming an image on a sheet conveyed by the sheet conveying unit;

a regulating unit provided so as to be slidable on the sheet container for regulating a set position of a sheet;

a position detector for detecting a position of the regulating unit; and

a contact detector for detecting a contact state between the uppermost layer of the sheets contained in the sheet container and the sheet conveying unit,

wherein the elevation/lowering driving unit lowers the sheet container when a change in the position of the regulating unit is detected by the position detector in a state in which the uppermost layer of the sheets contacts the sheet conveying unit;

Transfer of the control of the contr
and further comprising:
a receiving unit for receiving information according to a lowered amount of the sheet
container; and
a storage for storing the received information.
wherein the elevation/lowering driving unit lowers the sheet container by the lowered
amount stored in the storage when the position detector detects a change in the position of the
regulating unit.

17 (Original). The imag e forming apparatus according to Claim 16, wherein the elevation/lowering driving unit lowers the sheet container until the uppermost layer of the sheets and the sheet conveying unit are separated when the position detector detects a change in the position of the regulating unit.

Nagao et al. USSN 10/772,771 Page 7 of 11

18. Cancelled

19 (Original). The imag e forming apparatus according to Claim 16, further comprising a measuring unit for measuring a dimension of a sheet contained in the sheet container based on a detection result of the position detector.

20 (Original). The imag e forming apparatus according to Claim 16, further comprising a clocking unit, wherein the elevation/lowering driving unit elevates the sheet container when a change in the position of the regulating unit is not detected for a predetermined time.